




THERMATEX® Mercure



TECHNICAL PERFORMANCE

Building material class A2-s1, d0 as per EN 13501-1

Fire resistance F30 - F120 as per DIN 4102 part 2 (as per test certificate)

REI30 - REI120 per EN 13501 part 2 (as per test certificate)

Sound absorption EN ISO 354

 $\alpha_{\rm W}$ = 0.60 as per EN ISO 11654 NRC= 0.60 as per ASTM C 423

Sound attenuation $D_{h,f,w}$ = 34 dB as per EN ISO 10848 CAC = 36dB as per ASTM E413-10

(15 mm thickness, according to test certificate)

Light reflectance

Up to 88%

sound solution R_w= 21dB as per ISO 10140-2

Thermal conductivity $\lambda = 0.052 - 0.057$ W/mK as per DIN 52612


Air permeability PM1 (≤ 30 m³/hm²) as per DIN 18177

Humidity





Knauf AMF GmbH & Co. KG
Elsenthal 15
D-94481 Grafenau Germany
Telefon 08552 / 422-0 - Fax 08552 / 422-32
info@knaufamf.de - www.knaufamf.com



Due to reproduction processes colours shown in this catalogue may differ from the actual product colour. Product selection should always be made from AMF samples. All details and technical information stated in this brochure or other publicity material referring to AMF ceiling systems are based on test reports obtained under laboratory conditions. It is the responsibility of the customer to ensure that this data is suitable for the proposed application. All information provided is based on current technical data. Further relevant test reports, assessments and installation guidelines are available. All system details conform with current standards and are based on the use of AMF products and system components. AMF accepts no liability or responsibility for use of third party components, or for any variations to conditions stipula ted in test data. Mixing of production batches is not recommended. All technical data is subject to change without prior notice and is governed by AMF Terms and Conditions of Sales. This catalogue supersedes all previous editions. Errors and omissions excepted. Printing errors excepted.